

Package: progenyClust (via r-universe)

September 1, 2024

Type Package

Title Finding the Optimal Cluster Number Using Progeny Clustering

Version 1.2

Date 2016-04-08

Author C.W. Hu

Maintainer C.W. Hu <wendyhu001@gmail.com>

Description Implementing the Progeny Clustering algorithm, the 'progenyClust' package assesses the clustering stability and identifies the optimal clustering number for a given data matrix. It uses k-means clustering as a default, provides a tailored hierarchical clustering function, and can be customized to work with other clustering algorithms and different parameter settings. The package includes a main function `progenyClust()`, plot and summary methods for 'progenyClust' object, a function `hclust.progenyClust()` for hierarchical clustering, and two example datasets (`test` and `cell`) for testing.

License AGPL-3

Imports Hmisc

Depends graphics,stats,grDevices

NeedsCompilation no

Date/Publication 2016-04-12 20:04:15

Repository <https://huhuhuyeye.r-universe.dev>

RemoteUrl <https://github.com/cran/progenyClust>

RemoteRef HEAD

RemoteSha 21aa39e1a00741ed4eb09b2b7101c2d8058676e4

Contents

progenyClust-package	2
cell	3

hclust.progenyClust	3
plot.progenyClust	5
progenyClust	6
test	9
Index	10

progenyClust-package *Finding the Optimal Cluster Number Using Progeny Clustering*

Description

Implementing the Progeny Clustering algorithm based on Hu, Chenyue W., et al. "Progeny Clustering: A Method to Identify Biological Phenotypes." *Scientific Reports* 5 (2015), the progenyClust package assesses the clustering stability and identifies the optimal clustering number for a given data matrix. It uses kmeans clustering as default, but can be customized to work with other clustering algorithms and different parameter settings. The package includes one main function progenyClust(), plot and summary methods for "progenyClust" object, and two example dataset ("test" and "cell") for testing.

Details

Package: progenyclust
 Version: 1.1
 Date: 2015-11-24
 License: AGPL-3
 Imports: Hmisc
 Depends: graphics, stats

Author(s)

C.W. Hu, Rice University
 Maintainer: C.W. Hu <wendyhu001@gmail.com>

References

Hu, C.W., et al. "Progeny Clustering: A Method to Identify Biological Phenotypes." *Scientific reports* 5 (2015).
<http://www.nature.com/articles/srep12894>

`cell`*cell imaging metrics dataset*

Description

This cell dataset contains the first three principal components of the imaging metrics for 444 cells that were engineered into four patterns. The dataset therefore should include four clusters of cell samples in theory. See the references for more experimental and imaging analysis details of this data.

Usage

```
data("cell")
```

Format

A data frame with 444 observations on the following 3 variables.

PC1 The first principal component of imaging metrics

PC2 The second principal component of imaging metrics

PC3 The third principal component of imaging metrics

References

Slater, John, et al. "Recapitulation and Modulation of the Cellular Architecture of a User-Chosen Cell-of-Interest Using Cell-Derived, Biomimetic Patterning." *ACS nano* (2015).

Hu, C.W., et al. "Progeny Clustering: A Method to Identify Biological Phenotypes." *Scientific reports* 5 (2015).

Examples

```
data(cell)
```

`hclust.progenyClust`*Hierarchical Clustering*

Description

hierarchical clustering function for progeny clustering

Usage

```
hclust.progenyClust(x,k,h.method='ward.D2',dist='euclidean',p=2,...)
```

Arguments

x	a numeric matrix, data frame or <code>dist</code> object.
k	an integer specifying the number of clusters.
h.method	the agglomeration method to be used. This should be (an unambiguous abbreviation of) one of "ward.D", "ward.D2" (default), "single", "complete", "average" (= UPGMA), "mcquitty" (= WPGMA), "median" (= WPGMC) or "centroid" (= UPGMC).
dist	the distance measure to be used. This must be one of "euclidean", "maximum", "manhattan", "canberra", "binary" or "minkowski". Any unambiguous substring can be given.
p	The power of the Minkowski distance, when dist="minkowski".
...	additional arguments in <code>hclust(...)</code> .

Details

The function `hclust.progenyClust` mainly streamlines `dist`, `hclust` and `cutree` into one, and structures the output to be directly used by `progenyClust`. Most arguments and explanations were kept the same to ensure consistency and avoid confusion. For more details, please check each individual function.

Value

cluster	A vector of integers (from 1:k) indicating the cluster membership for each sample.
tree	An object of class <code>hclust</code> which describes the tree produced by the clustering process.
dist	A dissimilarity structure as produced by <code>dist</code> .

Author(s)

C.W. Hu, Rice University

References

Hu, C.W., et al. "Progeny Clustering: A Method to Identify Biological Phenotypes." *Scientific reports* 5 (2015).
<http://www.nature.com/articles/srep12894>

Examples

```
# a 3-cluster 2-dimensional example dataset
data('test')

# default progeny clustering
progenyClust(test, FUNclust=hclust.progenyClust, ncluster=2:5)->pc

# plot the scores to select the optimal cluster number
```

```

plot(pc)

# plot the clustering results with the optimal cluster number
plot(pc, test)

```

plot.progenyClust *Plot Progeny Clustering Results*

Description

Plot the cluster number selection results and visualizes the clustering results.

Usage

```

## S3 method for class 'progenyClust'
plot(x, data=NULL, k=NULL, errorbar=FALSE, xlab='', ylab='', ...)

```

Arguments

x	a progenyClust object.
data	the full or a subset of the original data matrix that was used for clustering. If unspecified, the function will plot stability scores for cluster number selection; If specified, the function will plot the data in scatter plots with colors annotated by clustering memberships (Please see details below).
k	integer specifying the cluster number for visualizing the clustering results of original data: only takes into effect when argument data is provided, and needs to be a cluster number that was previously investigated in progenyClust to generate the progenyClust object x. The default is the optimal number of clusters.
errorbar	logical flag: specifies whether the error bars should be drawn. The error bars can only be drawn when progeny clustering is repeated multiple times, i.e. input argument "repeats" in function progenyClust is greater than 1.
xlab	character string specifying the name of the x axis.
ylab	character string specifying the name of the y axis.
...	additional graphical arguments in plot(...) .

Details

The plot function provides two types of visualization: (1) visualizing stability scores, and (2) visualizing clustering results. To visualize the stability scores that are output from [progenyClust](#) function, please run the plot function without specifying the input argument data. The resulting plot visualizes the stability score at each cluster number. This plot can provide an overview of clustering stability, and can facilitate selecting the optimal cluster number.

The plot function can also visualize the clustering results in scatter plots by specifying the input argument data. Since the goal is to view how the original data is clustered with certain cluster number, data needs to contain exactly the same number of samples as in the original data that

was used to run the `progenyClust` function. If data contains more than two features, a table of scatter plots will be created to show clustering results within each pair of dimensions. data with more than 20 features/columns will not be accepted, but a subset of data with selected features can be used in this case. The input argument `k` specifies the cluster number at which the clustering result is shown. Note that `k` needs to be a cluster number that was previously examined by `progenyClust` when generating the `progenyClust` object `x`. If `k` is not provided, the function will use the optimal cluster number determined by the Gap criterion only if `method='gap'`, and will use the optimal number determined by the Score criterion if `method='gap'` or `method='both'` when running `progenyClust`.

Value

returns plots as described in Details.

Author(s)

C.W. Hu, Rice University

References

Hu, C.W., et al. "Progeny Clustering: A Method to Identify Biological Phenotypes." Scientific reports 5 (2015).
<http://www.nature.com/articles/srep12894>

Examples

```
# a 3-cluster 2-dimensional example dataset
data('test')

# default progeny clustering
progenyClust(test,ncluster=2:5)->pc

# plot the scores to select the optimal cluster number
plot(pc)

# plot the clustering results with the optimal cluster number
plot(pc,test)
```

progenyClust

Progeny Clustering

Description

Select the optimal number for clustering using Progeny Clustering.

Usage

```
progenyClust(data, FUNclust = kmeans, method = "gap", score.invert = F, ncluster = 2:10,
  size = 10, iteration = 100, repeats = 1, nrandom = 10, ...)
```

```
## S3 method for class 'progenyClust'
summary(object,...)
```

Arguments

data	data matrix or data frame for clustering: each row corresponds to a sample or observation, whereas each column corresponds to a feature or variable.
FUNclust	clustering function: accepts data as its first argument and the number for clustering as the second argument; returns a list containing a component called 'cluster' which is a vector of integers recording the clustering assignment for all samples. The default function is kmeans.
method	character string indicating the criterion used to pick the optimal cluster number. 'gap': the default value, selecting the cluster number that has the biggest or smallest (when score.invert=TRUE) gap from its neighboring numbrs. The optimal cluster number is picked based on the input data only, and is not compared against any random datasets, thus is quick to compute. Note that this method does not evaluate the minimum and maximum cluster numbers. 'score': selects the cluster number that has the highest or lowest (when score.invert=TRUE) score when comparing against scores generated from random datasets. Due to the repeats on progeny clustering on random datasets, this method is slower to compute. 'both': uses and outputs results from both the 'gap' and 'score' criteria.
score.invert	logical flag: specifies whether the score should be inverted. The default score is the ratio of true classification probabilities over false classification probabilities. The inverted score is the ratio of false classification over true classification probabilities, which can prevent the algorithm from generating infinite score values in cases of perfect clustering. When score.invert=TRUE, the optimal cluster number is picked based on the lowest score.
ncluster	sequence of integers specifying candidate cluster numbers for evaluation: ncluster needs to be continuous if the method 'gap' is chosen.
size	integer specifying the number of progenies generated from each cluster. Default value is 10.
iteration	integer specifying the number of times the algorithm samples progenies and evaluates similarity among progenies. Default value is 100.
repeats	integer specifying the number of times the algorithm should be run: needs to be greater than 0. Values greater than 1 output standard deviations of the scores, which are plotted as error bars in print(...,errorbar=T,...) function. Default value is 1.
nrandom	integer specifying the number of random datasets used to generate reference scores when using method 'score'. Default value is 10.
object	the S3 object of class "progenyClust".

... additional arguments for FUNclust in progenyClust(...).

Value

progenyClust returns an object of class "progenyClust" which has a plot and summary method. It is a list with the following components:

cluster	matrix of clustering memberships for all samples under given cluster numbers: each row corresponds to a sample; each column corresponds to a given cluster number.
score	matrix of stability scores from clustering the input data under given cluster numbers: each column corresponds to a given cluster number; each row corresponds to a repeat, the number of which is defined by 'repeats' in the input argument.
random.score	matrix of stability scores from clustering random datasets under given cluster numbers: each column corresponds to a given cluster number; each row corresponds to a random dataset, the number of which is defined by 'nrandom' in the input argument.
random.score	matrix of stability scores from clustering random datasets under given cluster numbers: each column corresponds to a given cluster number; each row corresponds to a random dataset, the number of which is defined by 'nrandom' in the input argument.
mean.gap	vector of mean stability scores based on the 'gap' criterion when the input argument 'method' is set to be 'gap' or 'both'.
mean.score	vector of mean stability scores based on the 'score' criterion when the input argument 'method' is set to be 'score' or 'both'.
sd.gap	vector of standard deviations of stability scores for each given cluster number based on the 'gap' criterion, when the input argument 'method' is set to be 'gap' or 'both'.
sd.score	vector of standard deviations of stability scores for each given cluster number based on the 'score' criterion, when the input argument 'method' is set to be 'score' or 'both'.
call	the call with arguments specified.
ncluster	the specified value of input argument 'ncluster'.
method	the specified value of input argument 'method'.
score.invert	the specified value of input argument 'score.invert'.

Author(s)

C.W. Hu, Rice University

References

Hu, C.W., et al. "Progeny Clustering: A Method to Identify Biological Phenotypes." Scientific reports 5 (2015).
<http://www.nature.com/articles/srep12894>

Examples

```
# a 3-cluster 2-dimensional example dataset
data('test')

# default progeny clustering
progenyClust(test,ncluster=2:5)->pc

summary(pc)
plot(pc)
```

test

3-cluster 2-dimensional test dataset

Description

This test dataset contains 3 clusters centered around (-1,2),(2,0) and (-1,-2) in a 2-dimensional space. Each cluster consists of 50 samples that were drawn from bivariate normal distributions with a common identity covariance matrix.

Usage

```
data("test")
```

Format

A data frame with 150 observations on the following 2 variables.

V1 numeric vector of coordinates in x axis

V2 numeric vector of coordinates in y axis

References

Hu, C.W., et al. "Progeny Clustering: A Method to Identify Biological Phenotypes." Scientific reports 5 (2015).
<http://www.nature.com/articles/srep12894>

Examples

```
data(test)
```

Index

- * **cluster**
 - hclust.progenyClust, 3
 - plot.progenyClust, 5
 - progenyClust, 6
- * **datasets**
 - cell, 3
 - test, 9
- * **hierarchical**
 - hclust.progenyClust, 3
- * **package**
 - progenyClust-package, 2
- * **plot**
 - hclust.progenyClust, 3
 - plot.progenyClust, 5

cell, 3

cutree, 4

dist, 4

hclust, 4

hclust.progenyClust, 3

plot, 5

plot.progenyClust, 5

print.summary.progenyClust
 (progenyClust), 6

progenyClust, 4–6, 6

progenyClust-package, 2

summary.progenyClust (progenyClust), 6

test, 9